

Product Specification for Unbranded Computer Table consists of Computer table with key board drawer and table top		
Specification  विनिर्देश	Sub-Spec  उप-विनिर्देश	Value  मूल्य
GENERIC	Type of Computer Table	Computer table with key board drawer and table top
	Construction of Computer / Printer Table	Steel members duly welded and rigid fixed table top,with slideable key board tray,drawer,modesty panel,foot rest and also with another shelf at the bottom side for placing CPU and other peripherals
	Top Extended by	50 mm on all sides over the steel frame
	Edge of Top	banded with 1.5 mm thick PVC tapes of some shade as that of tape
	Placing of modesty panel	covering full back side of frame end suitably welded with two side members of the from in such a way that it's top surface having 17 mm width,flushes with top surface two side members and joining front angle member
	Packing	Corrugated Plywood
	Mode of Supply of modular table	Assembled Ready To Use
MATERIAL	Frame Material Size	Hollow Rectangular Section Of Size 50 X 25 X 1.6 Mm Thick
	Frame material of foot rest	Hollow Rectangular Section Size 50 X 25 X 1.6 Mm Thick
	Joining of Frame	two side member of the frame identical in shape joined with welding at bottom with a footrest angularly welded
	Welding of Modesty Panel	A modesty panel of size 200 mm X 17 mm X 0.8 mm thick CRC sheet to be welded
	Making of Frame	To be rigid in construction
	Welding at top and Back	At The Top In Front Side Welded With An Angle Size 17 Mm X 17 Mm X 3 Mm And At The Back On The Top Side Of The Frame
	Guides Thickness (for drawer)	2 mm thick minimum from mild steel sheet
	Material of Table Top, Key board and drawer	pre-laminated Particle boards (Wood Product) of grade II Type II of IS 12823 Latest
	Bottom side of top	should have balancing sheet of requisite thickness of same colour as top laminate
	Thickness of Table Top etc	18 millimeter
	Lock of Drawer	No
	Type of lock	N.A
	Sliding of Key board	provided with two telescopic channels with balls
	Material of Modesty Panel	N.A
	Welding of screws to make capable to adjustable level upto 10 mm in height	four level screws, having smooth bottom flat surface of minimum 50 mm diameter, be welded under the bottom of two side members of frame
DIMENSION	Size of Computer Table ±10 mm (LXBXH)	900 Mm X 600 Mm X 750 Mm
	Size of Printer Table ±10 mm (LXBXH)	NA
	Size of Computer Cum Printer Table ±10 mm (LXBXH)	NA
	Outside Drawer Size (L X B X H) ±5 mm	NA
	Size of key board tray ±5 mm	600 mm (front width) X 500 mm (depth) provided with end fitting made from 2 mm thick MS steel mounted on either side
	Size of Modesty panel	200 mm X 17 mm X (0.8 mm thick)
COLOUR & FINISH	Phosphating treatment of MS parts after Pick	as per IS:3618/Latest
	Primer for coating on M S parts	Zinc-chromate
	Putty for filling	conforming to IS:110/Latest
	Paint	exposed steel sections to be painted with black in colour with powder coating 40-50 micron thickness
	Powder Coating	conforming to IS:13871/Latest
	Colour of Top	peach
WARRANTY	Warranty period in number of years	1
CERTIFICATION	Test reports to be furnished to buyer on demand	NO